



# TWIN-HEAD BENDERS

**CR-T38D**



- Proportional pressure controlled hydraulic driven rotation of wiper around the bend die
- Hydraulic clamping of the tube between bend die and clamp block
- Hydraulic actuation of pressure die
- Adjustable bending angles from 0° - 180°
- Heads can be set to bend two different angles in the same part
- Automatic or Manual operation
- Head speeds controlled individually
- Easily accessible multiple emergency stops
- Adjustable timing between each motion




**CR-T50D** (SHOWN W/ OPTIONAL SAFETY PACKAGE)

## Machine Specifications

Model	CR-T38D	CR-T50D
Maximum Capacity (Mild Steel)	ø1½" x .078"	ø2" x .095"
Range of Radius	1" - 6⅝"	1⅜" - 8"
Range of Bending Angle	0° - 180°	0° - 180°
Distance Between Heads	6" - 36"	7" - 78"
Power	7½ HP	10 HP
Maximum Bending Speed	90°/ 5-6 Sec.	90°/ 5-6 Sec.
Dimensions (L x W x H)	95" x 38" x 79"	98" x 42" x 79"
Floor space length at Max. head distance	126"	170"
Weight	3,100 lbs	3,970 lbs.

*Note: Technical data and machine design subject to change without notice.*



## J&S Machine, Inc.

W6009 490<sup>th</sup> Avenue  
 Ph: 715-273-3376  
 E-mail: [sales@jsmachine.com](mailto:sales@jsmachine.com)

Ellsworth, WI 54011  
 Fax: 715-273-5241  
 Web site: [www.jsmachine.com](http://www.jsmachine.com)

